

Lollipop Thermometer

Models: DTL572-Y (Yellow), DTL572-R (Red), DTL572-G (Green), DTL572-B (Blue)

This full-featured thermometer offers an IPX7 waterproof rating, 4.3-inch stem, 1.5 mm thin tip, fast 4-second response and one-button field calibration. Hold and max/min modes.



Features	Hold, max/min, on/off button, auto-off, selectable units
Measurement Range	-40 to +572°F/-40 to 300°C
Unit of Measure	°F (°C)
Accuracy	±1.3°F (0.72°C)
Calibration	One-button field calibration
Heat Resilience	High heat
Water Resilience	IPX7: protected from water up to 3 feet (1 meter) for 30 minutes
Response Time	4-second response
On/Off	On/off button
Auto-off	Auto-off after 10 minutes
Housing Material	Food-safe ABS
Display Material	LCD, high contrast
Display Size	1.08 W x 0.52 H in (2.74 W x 1.33 H cm)
Digit Height	9 mm
Probe Type	Thermistor
Probe Material	304 stainless steel
Probe Length	4.3" (11.0 cm) stem
Probe Diameter	1.5 mm thin tip
Resolution	0.1°F (0.1°C)
Casing	Sheath
Mounting	Pocket clip
Temperature Guide	USDA safe food temperature guide on sheath
Operating Range	32 to 104°F (0 to 40°C), ≤90% RH
Battery	Two LR44 alkaline button batteries included
Battery Life	10 months (3 times/day, 5 sec/time)
Dimensions	1.6 W x 6.9 H x 0.7 D in (4.08 W x 17.48 H x 1.77 D cm)
Weight	1.06 oz (30 g) (including battery)
UPC	DTL572-Y: 0 18436 00511 7, DTL572-R: 0 18436 00512 4, DTL572-G: 0 18436 00513 1, DTL572-B: 0 18436 00514 8
Certification	NSF [®] Certified, WEEE, CE
Antimicrobial Protection	BioCote [®] antimicrobial
Warranty	5-Year Limited Warranty