

## **Thermocouple Thermometers**

## **Folding Thermocouple Thermometer**

Model: TCT572-W (White), TCT572-BK (Black), TCT572-R (Red)

Compact folding thermocouple with rapid response and 1.5 mm thin tip probe. Field recalibratable. Stores max/min temperatures and is extremely durable.



Features	Max/min, backlit display, extra-big digit, on/off switch, auto-off, selectable units
Measurement Range	-58 to +572°F/-50 to +300°C
Unit of Measure	°F (°C)
Accuracy	±1°F (0.5°C)
Calibration	Field calibration
Water Resilience	IPX4: protected from water splashes from any direction (except case/probe junction)
Response Time	3-second response
On/Off	On/off button
Auto-off	Auto-off after 10 minutes
Housing Material	Food-safe ABS
Display Material	LCD
Display Size	1.875 W x 0.75 H in (4.8 W x 1.9 H cm)
Probe Type	Thermocouple Type K
Probe Material	304 stainless steel
Probe Length	4.25" (10.8 cm)
Sensor Diameter	1.5 mm thin tip
Resolution	0.1°F (0.1°C)
Operating Range	32 to 104°F (0 to 40°C), ≤90% RH
Battery	Two CR2032 lithium button batteries included
Battery Life	404 days
Dimensions	1.625 W x 2.25 H x 0.5 D in (4.1 W x 5.7 H x 1.3 D cm)
Weight	2.4 oz (68 g) (including battery)
UPC	TCT572-W: 0 18436 00464 6, TCT572-BK: 0 18436 00465 3, TCT572-R: 0 18436 00466 0
Certification	NSF® Certified, WEEE, CE
Antimicrobial Protection	BioCote® antimicrobial
Warranty	5-Year Limited Warranty



© 11-2023 CDN CD2921100 - 11/23