

REFRIGERATOR/FREEZER THERMOMETER

 Frost buildup makes it harder for the freezer to maintain the proper temperature. Defrost when

To preserve taste and texture of food, freeze quickly

Air causes freezer burn by removing moisture from

food. Seal food securely with a good quality wrap

 Do not put a large quantity of unfrozen food into the freezer all at once. This could partially thaw the food already in the freezer by raising freezer

 Check the rubber seal on the door periodically to make sure that cold air is not leaking out. Close

the door on a dollar bill. If the bill can be withdrawn easily without opening the door, consider having

-40 to +80°F/-40 to +27°C

FOR MONITORING REFRIGERATOR OR FREEZER TEMPERATURES

- NSF® Certified
- Target range indication
- Shatterproof case
- Non-mercuric column
- Temperature guide on thermometer
- 2-way mounting: stand/hang



Note: The red liquid in the thermometer is food-safe oil.

FOOD SAFETY DURING POWER OUTAGES

Refrigerator – keep 40°F/4°C or lower

4 hours if closed

the seal replaced.

TIPS

necessary.

or container.

temperature.

and thaw slowly.

- 2 hours once above 40°F/4°C
- 1 hour in hot weather 90°F/32°C

Freezer – keep 0°F/-18°C or lower

- 48 hours if full and closed
- 24 hours if half-full and closed
- 50 lbs. of dry ice should hold an 18-cubic foot fully-stocked freezer cold for 2 days
- © 2020 http://www.foodsafety.gov/keep/emergency/index.html

CONSERVE ENERGY BY MAINTAINING PROPER TEMPERATURES!

Food will not keep as well, or as long, if it is not kept at the proper temperature. The FG80 is designed to measure refrigerator and freezer temperatures reliably and accurately. Use it to make sure that your refrigerator and freezer are kept at the proper temperature for better food storage and energy conservation.





The information in this document has been reviewed and is believed to be accurate. However, neither the manufacturer nor its affiliates assume any responsibility for inaccuracies, errors or omissions that may be contained herein. In no event will the manufacturer or its affiliates be liable for direct, indirect, special, incidental or consequential damages arisen by using this product or resulting from any defect/omission in this document, even if advised of the possibility of such damages. The manufacturer and its affiliates reserve the right to make improvements or changes to this document and the products and services described at any time, without notice or obligation.



5-Year Limited Warranty: Any instrument that proves to be defective in material or workmanship (excluding batteries) within five years of original purchase will be repaired or replaced without charge upon receipt of the unit prepaid at: CDN, PO Box 10947, Portland, OR 97296-0947 USA. This warranty does not cover damage in shipment or failure caused by failure to adhere to the accompanying instructions, inadequate maintenance, normal wear and tear, tampering, accident, misuse, unauthorized modification, obvious carelessness or abuse. CDN shall not be liable for any consequential or incidental damages whatsoever.

For more detailed information on our products, please visit CDNmeasurement.com or call 800-338-5594.

