

## Digital High Precision Scale, 2 lb

**Model: SD0204**

This exclusive NSF<sup>®</sup> Certified scale was designed for demanding foodservice kitchens. It is precise to a hundredth of an ounce or one tenth of a gram. Featuring tare, hold and field calibration to ensure accuracy over time, it offers a small profile and BioCote<sup>®</sup> antimicrobial technology. Batteries and power adapter included.



Features	Small profile, selectable units, tare function, hold, field calibration, overload indication, battery status indication, removable stainless steel platform, on/off button, AC adapter
Measurement Range	2 lb/1 kg capacity
Unit of Measure	lb:oz/kg.g
Resolution	0.01 oz, 0.1 g
Accuracy	500g ±1.5 g; 1000g ±3 g
Tare	Tare function
Calibration	Field calibration
Water Resilience	IP54: protected from water splashes from any direction for 10 minutes; dust protected
Response Time	0.125 second response
On/Off	On/off button
Auto-off	Auto-off after 2 minutes; disabled when the AC adapter is used
Housing Material	Food-safe ABS plastic
Display Material	LCD
Display Size	3.35 W x 0.866 H (in)/8.5 W x 2.2 H (cm)
Load Cell	Single point load cell
Platform Material	304 stainless steel
Platform Size	5.35 W x 5.35 L (in)/13.6 W x 13.6 L (cm), removable
Operating Range	32 to 104°F/0 to 40°C ≤90% RH
Power	AC Adapter: 100-240 VAC 50/60 Hz input, 9V DC (500mA) output
Battery	Two AAA alkaline batteries (WERCSmart) included
Battery Life	1 year (3 times/day, 120 s/time)
Dimensions	5.90 W x 1.75 H x 7.87 D (in)/15.0 W x 4.45 H x 20.0 D (cm)
Weight	18.5 oz / 524 g (including battery)
UPC	0 18436 00839 2
Certification	NSF <sup>®</sup> Certified, WEEE, CE
Antimicrobial Protection	BioCote <sup>®</sup>
Warranty	1-Year Limited Warranty
Optional Accessories	1 kg calibration weight (WT01), Small Profile Platform (AD-PF0502), Power Adapter (AD-AC3302)
Replacement Parts	Small Profile Platform (AD-PF0502), Power Adapter (AD-AC3302)

