

## SUBMERSIBLE SCALE, 22 LB

The newest member of the *Submersible Scales* series, the Submersible Scale, 22 lb (SD2220) was designed for demanding foodservice kitchens. It is NSF<sup>®</sup> Certified, sturdy and programmable, featuring low/high limit alerts with the color-coded backlit display. The heavy-duty stainless steel SD2220 is submersible with an impressive IP68 rating, which certifies it to be protected from water up to 4.9 feet (1.5 meter) for 60 minutes and completely protected against dust. Also available in an 11 pound capacity.



### FEATURES

- NSF<sup>®</sup> Certified
- Low/high limit alerts with backlit display
- Submersible (IP68: protected from water up to 4.9 feet (1.5 meter) for 60 minutes, completely protected against dust)
- Programmable
- Tare
- Hold
- Field calibration
- Removable stainless steel platform
- Stainless steel housing
- Rechargeable battery, AC adapter & instructions included

### SPECIFICATIONS

<b>Measurement Range:</b>	22 lb/10 kg/352 oz by oz, / oz, kg, g, lb:oz, lb:/ oz, lb
<b>Display Size:</b>	3.35 W x 1.3 H in (8.5 W x 3.3 H cm)
<b>Platform Size:</b>	6.4 W x 7 L in (16.2 W x 18.2 L cm)
<b>Product Dimensions:</b>	8.0 W x 2.0 H x 10.0 D in (20.3 W x 5.0 H x 25.1 D cm)
<b>Resolution:</b>	0.05 oz, 1/8 oz, 0.001 kg, 1 g, 0 lb:0.1 oz, 0 lb:1/8 oz, 0.002 lb
<b>Power:</b>	AC Adapter: 100-240 VAC 50/60Hz input, 9V DC (1000mAh) output included; Battery: built-in rechargeable 4.8V 1800 mAh included
<b>Weight:</b>	46.31 oz (1313 g)
<b>UPC:</b>	0 18436 00846 0
<b>Other:</b>	<ul style="list-style-type: none"> <li>• Selectable units</li> <li>• Stability indication</li> <li>• Overload indication</li> <li>• Low battery &amp; charging indication</li> <li>• On/off button</li> <li>• Auto-off after 2 minutes, programmable to 5 minutes; disabled when AC adapter used</li> </ul>

### AVAILABLE

Now shipping

